

## **Scandinavia Corn Roast Tractor Pull Rules**

**(Antique, Classic, Near Stock)**

**\$20.00 Per Hook**

1. FOR SAFETY REASONS – NO ONE OTHER THAN DRIVER ALLOWED ON TRACTOR ANYWHERE ON SHOW GROUNDS!
2. No alcoholic beverages on track or pit area, any driver believed to be a potential safety hazard will be disqualified.
3. Tractors must be operated in a safe manner at all times. Anyone driving recklessly or caught tampering with another person's tractor will be disqualified from pulling.
4. 2 Limit hook per tractor.
5. One pull allowed per tractor in each class unless the track judge rules otherwise or if a tie is declared in the top placing tractors. If disqualification is ruled on top placing tractor, all other tractors move up one place.
6. Any tractor violating the track boundary will be disqualified. The decision of the track judge will be final.
7. Drivers must be 14 years of age or older. All drivers enter at own risk. Drivers between the age of 14 and 18 must have parent's written consent and safety class certificate with them. NO EXCEPTIONS!!!
8. Tractors will be stopped if the front end raises higher than the track judge decides is safe.
9. Extra weights must be securely fastened to the tractor. If anything falls off before the pin is pulled, the tractor will be disqualified.
10. Any gas-operated tractor must use gasoline only.
11. While pulling the driver must remain on the seat (if so equipped) with one hand on the wheel. No jumping or bouncing will be allowed, however, leaning will be allowed.
12. Tractors must stop immediately upon red flag signal from the judge or be disqualified. If puller is stopped by track judge for any reason, puller takes the distance where he/she stopped except if it is the first ten feet. If stopped within the first ten feet, puller is entitled to a restart.
13. Tractors must be wheel driven, no crawlers or dual wheels, NO FWD.
14. Puller must furnish own clevis or pullers' eye to accept eliminators hook. (MINIMUM 2.5" HOLE. PULLING POINT CAN BE NO MORE THAN 1.5" FROM THE BACK EDGE OF HITCHING DEVICE.)
15. Steel wheels will pull last in class, use of extension rims allowed.
16. Tractors with draw bar closer than 32" to set center of rear axle must have wheelie bars, kill switch and fenders.
17. Weigh-in NO OVERAGE. After pull, 50 pounds over accepted. If you are 51 pounds over, you will be disqualified!

**TRACK JUDGES RULING IS FINAL ON ALL AREAS OF DISPUTE NOT COVERED IN THESE RULES!**

### **ANTIQUÉ**

1. Must be 1938 or older paced at 3.5 MPH.  
Weight classes: 4000, 4500, 5000, 6000, 7000, 8000 and 12,000.  
Max tire size:           4000 – 14.9"  
                                  4500, 5000 – 15.5"  
                                  6000, 7000, 8000, 12000 – 18.4"
2. Front weights shall not exceed more than 24" beyond the center of the front frames outmost casting.  
Rear weights not to exceed 24" behind center rear axle.
3. Rigid draw bar must not exceed 20" in height, cannot be closer than 18" from the center of the rear axle.

## CLASSIC

1. Must be 1939 thru 1957 paced at 3.5 MPH.

Weight classes: 3500 and under, 4000, 5000, 6000, 7000, and 12000.

Max tire size: 3500 – 13.6”

4000 – 15.5”

5000 – 16.9”

6000, 7000, 12000 – 18.4”

2. Front weights shall not exceed more than 24” beyond the center of the front frames outmost casting. Rear weights not to exceed 24” behind center rear axle.
3. Rigid draw bar must not exceed 20” in height, nor can be closer than 18” from the center of the rear axle.
4. Engine speed must be controlled by the throttle lever and a functional stock governor only. No strings, wires or foot feeds allowed. Decision of the track judge is final. 20% over RPMS will be allowed. RPM LIMITS ENFORCED!

## NEAR STOCK

1. Must be 1957 or older – low gear only.

Weight classes: 3500, 4000, 4500, 5000, 6000, 6500, and 7000. Must be within manufacturer’s H.P. and RPM’s.

Max tire size: 4000 & 5000 – 15.5”

2. Engine, stock block, head, manifold, carburetor (by part #), no add-on parts not in original parts book. No electronic ignitions, stock coil only. Stock hp and RPM’s.
3. Tractors must have original, or as close to original size tires, rims, cut-down steel is ok. No 18.4” tires will be allowed.
4. Original hitch/drawbar hole must be no closer than 32” from center of rear axle, allowances will be made on certain models, maximum height 20” and must be rigid.
5. Tractors must have stock appearance.
6. No cut or sharpened tires.
7. Must have original air cleaner, if one is used.
8. No weight brackets. Weights will only be allowed if placed on wheels.
9. No radial tires.
10. RPM LIMITS ENFORCED!

## 8 MPH PACE

1. Must be 1957 or older.

Weight classes: 3750, 4250, 4750, 5750, 6750.

Max tire size: 18.4”

2. Must run stock block, transmission, rear-end, sheet metal, etc.
3. Cut tires are allowed.
4. Wheelie bars, kill switch and fenders MANDATORY!
5. RPM’s over 20% must have safety equipment (safety blanket, scatter shield, steel flywheel, fan shroud or side shields, etc.)
6. NO TROPHIES, 100% PAYBACK FOR FIRST, SECOND and THIRD PLACING.

Rigid draw bar **MUST**  
support weight of tractor